

## PATTERN 7656

### PATTERN PIECES:

A B	1	Vord. Hosenteil 2x
A B	2	Taschenbeutel 2x
A B	3	Hüftpassenteil 2x
A B	4	Rückw. Hosenteil 2x
A B	5	Vord. Bund 4x
A B	6	Rückw. Bund 4x
A	7	Vord. Blende 4x
A	8	Rückw. Blende 4x
A	9	Tasche 2x
A	10	Schlaufen 1x

THE CUTTING LAYOUTS ARE ON THE PATTERN SHEET

### PREPARING PATTERN PIECES

Choose your size according to the Burda measurement chart: dresses, blouses, jackets, and coats according to your bust measurement and pants and skirts according to your hip measurement. Adjust the pattern pieces, if necessary, by adding or subtracting the number of inches (cm) that your measurements differ from the measurements given in the Burda chart.

#### AB

Cut out the following pattern pieces in the required size: for the PANTS, view **A**, pieces 1 to 10 and for the PANTS, view **B**, pieces 1 to 6.

➔ The upper waistband edge sits at waist level.

#### Sizes 10 to 20 (36 to 46)

Mark the stitching line for the zipper on pattern piece 1 the same distance from center front as marked for size 8 (34), angling in to slit mark.

**A:** Mark buttonholes on pattern piece 7 the same distance from side edge as marked for size 8 (34).

### LENGTHENING OR SHORTENING PATTERN

Our pattern is calculated for a height of 5 feet, 6 inches (168 cm). If you are taller or shorter, you may adjust the pattern to fit your size at the lines marked "lengthen or shorten here". This ensures proper fit.

➔ Make sure that you adjust all pieces of one model by the same amount at the same lines.

#### How to lengthen or shorten pattern pieces:

Cut pattern pieces along marked lines.

**To lengthen**, slide the two halves of the pattern piece as far apart as necessary.

**To shorten**, overlap the two halves of the pattern piece as far as necessary.

Even out side edges.

### CUTTING

**FOLD** (---) means: Here is the center of a pattern piece, but in no case a cut edge or a seam. The piece should be cut double, with the fold line forming the center line.

Pattern pieces that are outlined with a broken line in the cutting layout are to be placed face down on the fabric.

**The cutting layouts on the pattern sheet show how the pattern pieces should be placed on the fabric.**

#### AB

When cutting from a single layer of fabric, the pattern pieces are pinned to the right side. For double layers of fabric, the right sides are facing and the pattern pieces are pinned to the wrong side. The pattern pieces that are shown in the cutting layout extending over the fold of the fabric should be cut last from a single layer of fabric.

#### SEAM AND HEM ALLOWANCES must be added:

$\frac{5}{8}$ " (1.5 cm) for hem and at all other seams and edges, except on piece 10 for view **A** (allowances already included).

Transfer all pattern outlines (seam and hem lines) and pattern markings to wrong side of fabric pieces using BURDA dress-maker's carbon paper. Follow instructions included with carbon paper.

#### INTERFACING

Cut out interfacing pieces as illustrated and iron to wrong side of fabric pieces. Transfer pattern outlines to interfacing pieces.

### SEWING

**When sewing pieces together, right sides of fabric should be facing.**

Hand baste along pattern markings to make them visible on the right side of the fabric pieces.

#### AB

##### Tips for sewing stretch blend fabrics

Use a special sewing machine needle for stretch fabrics. To keep seams elastic, stitch them with a narrow zigzag stitch (1 mm wide, approx. 2.5 mm long) or with a special stretch stitch (see your machine's instruction manual). Make sure that the thread tension is not set too tight.

#### AB

##### PANTS

Baste **darts** in pants backs. Stitch each dart from edge toward point. Knot threads at points of darts. Press darts toward center back.

##### Hip yoke pockets

**1** Lay each pocket piece on pants front, right sides facing. Baste together along pocket opening edge, matching seam numbers (1), and stitch. Trim seam allowances and clip into corner (arrow). Turn pocket to inside and baste. Press seamed edge. Topstitch close to seamed edge and  $\frac{1}{4}$ " (0.7 cm) from seamed edge (1a).

**2** Pin pants front to hip yoke piece so that pocket opening edge meets marked **PLACEMENT LINE**. The right sides of pocket and hip yoke pieces should be facing. Slide pocket opening slightly open and baste. At corner, stitch small, closely spaced zigzag stitches, at an angle, between stitching lines, as illustrated.

**3** Baste pocket to hip yoke piece, making sure to **not** catch pants front. Stitch. Finish edges of seam allowances together. Baste side, upper, and front edges of hip yoke piece to pants front. **Attention:** On **right** hip yoke piece, trim away seam allowance on front edge, along marked center front (arrow).

#### A

##### Pockets / pants backs

**4** Finish edge of self-facing on upper edge of each pocket piece. Press self-facing to wrong side. Trim allowances on side and lower edges to  $\frac{1}{4}$ " (0.7 cm) wide. Finish edges of allowances on these edges, turn to wrong side, baste, and press.

**5** Baste pockets to pants backs to meet marked placement lines. Topstitch close to side and lower edges and  $\frac{1}{4}$ " (0.7 cm) from these edges to attach.

#### AB

##### Side seams / Inner leg seams

**6** Lay pants fronts on pants backs, right sides facing. Baste side seams, matching seam numbers (2), and inner leg seams, matching seam numbers (3), and stitch. Finish edges of seam allowances and press seams open.

## Pattern 7656

### AB

#### Center front seam

**7** Turn one pant leg right side out. Pull this pant leg into the other, right sides facing. Stitch center seam from slit mark to inner leg seams. Tie-off ends of seam. Trim seam allowances of curve. Finish edges of seam allowances, including those on front facings.

#### Zipper

**8** On **right** pants front, turn **FACING** to inside along marked center front and baste.

➔ On **left** pants front, leave the facing extending  $\frac{3}{8}$ " (1 cm) wide as underlap so that the zipper will be covered. Turn remaining facing to inside, baste, and press.

**9** Baste underlap to zipper tape, directly next to zipper teeth and edgestitch in place.

**10** Close zipper. Pin fly closed, matching center fronts.

**11** Baste zipper tape to right facing, making sure to **not** catch pants front. Stitch.

**12** Topstitch **right** slit edge as marked, thereby catching the facing.

#### Waistband

**13** Lay interfaced front waistband pieces on interfaced back waistband piece, right sides together. Stitch side seams, matching seam numbers (4). Press seams open.

Stitch side seams on waistband pieces with no interfacing in same manner.

**14** Baste interfaced waistband unit to upper edge of pants, right sides together, matching center fronts and center backs. Seam numbers (5) must match and side seams must match. Stitch. Trim allowances. Press allowances toward waistband. Finish lower edge of remaining waistband unit.

**15** Lay waistband unit with no interfacing on attached, interfaced, waistband unit, right sides together. Press lower allowance to wrong side in area of front edges. Stitch together along upper and front edges – stitching at center front on **right front edge** and at underlap on **left front edge**. Trim seam allowances, trimming corners diagonally. Turn waistband right side out and turn up at center back.

#### Center back seam

Pull one pant leg into the other again, right sides facing.

**16** Baste center back seam on pants and waistband. Stitch seam. Finish edges of seam allowances and press seam open from upper edge to beginning of curve.

**17** Turn waistband to inside. Baste edges and press. Topstitch close to edges of waistband, thereby catching inner edge. Work **BUTTONHOLE** in right front end of waistband. Sew **BUTTON** to underlap to match buttonhole.

### A

#### Loops

**18** Finish long edges of loop strip. Press long edges to wrong side  $\frac{3}{8}$ " (1 cm) wide. Topstitch close to fold edges. Cut strip into 5 equal pieces. Finish ends of loop pieces.

**19** Pin loops pieces to waistband attachment seam, placing them at front pocket openings, at back darts, and over center back seam. Stitch loop pieces in place as illustrated. Turn loops up, turn ends under, and edgestitch to upper edge of waistband. **TIP:** If you plan on wearing a narrow belt, topstitch  $\frac{3}{8}$ " (1 cm) from upper and lower edges of loops (19a).

#### Bands

**20** Lay interfaced front band pieces on interfaced back band pieces, right sides facing. Stitch inner leg seams, matching seam numbers (6).

Trim seam allowances and press seams open.

Stitch seams on band pieces with no interfacing in same manner.

**21** Pin each interfaced band unit to band unit with no interfacing, right sides together. Baste together on lower edge and narrow edges and stitch. Trim seam allowances, trimming diagonally across corners.

Turn bands right side out. Baste seamed edges and press. Work **BUTTONHOLES** in edges of bands as marked.

Pin front edge of each band to back edge, to meet marked placement line. Baste upper edges together (21a).

**22** Baste bands to lower edges of pant legs, right sides facing, matching seam numbers (7) and matching inner leg seams. The closure edges with buttonholes must meet side seams. Stitch. Trim seam allowances. Finish edges of allowances together and press up. Topstitch pant legs close to attachment seams and  $\frac{1}{4}$ " (0.7 cm) from attachment seams, thereby catching allowances. Sew **BUTTONS** in place to match buttonholes.

### B

#### Hem

**23** Finish lower edge of each pant leg. Turn hem allowance to inside, baste, and press. Topstitch  $\frac{1}{2}$ " (1.2 cm) from fold edge, thereby catching the hem.